


MAINTENANCE OPERATIONS STANDARD PRACTICE

Work Order Standard Operating Practice

INSTRUCTION NUMBER: 75-0008

VII. WORK ORDER CREATION PROCESS (MAKE READY TYPE)

MAKE READY Type work orders require the selection of a applicable make ready **TASK #**. After a Task # selection is made it will automatically populate the Work Procedures table and Brief Description field.







MAINTENANCE OPERATIONS STANDARD PRACTICE

Work Order Standard Operating Practice

INSTRUCTION NUMBER: 75-0008

WORK ORDER CREATION PROCESS (MAKE READY TYPE) - Cont.

The work procedures are specific and the required steps are listed in order. Each of these boxes should be checked off to insure all proper steps for the make ready are completed. All of these steps are taken from the asset's Standard Operating Procedures manual.

| Edit | Options | | | | | | |
|-----------|--------------------------------|---|------------|---|-----|------------------------|---------------------|
| Luit | Seq. Task Description | Detail Task Description | Comments D | | OK? | Needs Repair (Insp) | Document Storage |
| То | 1.00 TRAILER | Check for valid registration and that it is in an approved document holder | | | | | |
| То | 2.00 TRAILER | Check for valid state/ federal annual inspection (If applicable) | | | | | |
| To | 3.00 TRAILER | Check the trailer tongue jack for proper operation | | | | | |
| To | 4.00 TRAILER | Inspect trailer tongue coupler | | | | | |
| То | 5.00 TRAILER | Check safety chains and hooks | | | | | |
| To | 6.00 TRAILER | Check breakaway cable and hook | | | | | |
| То | 7.00 TRAILER | Check Trailer light connector and verify it is in good condition | | | | | |
| To | 8.00 TRAILER | Check hydraulic brake fluid level | | | | | |
| То | 9.00 TRAILER | Check brake lines for leaks | | | | | |
| То | 10.00 TRAILER | Check trailer brakes for proper operation/adjustment | | | | | |
| То | 11.00 TRAILER | Check Trailer Lights for proper operation | | | | | |
| To | 12.00 TRAILER | Check all wheel bearings, grease/oil level, and ensure the dust caps are in place | | | | | |
| То | 13.00 TRAILER | Check tire tread depth (Must be over 4/32nd) | | | | | |
| То | 14.00 TRAILER | Check tire pressure (set to manufactures recommended pressure) | | | | | |
| То | 15.00 TRAILER | All Lug nuts torqued to 100 ft. lbs | | | | | |
| Го | 16.00 TRAILER | Check mud flap condition (If applicable) | | ā | | | |
| Го | 17.00 TRAILER | Check for fire extinguisher mounting/ inspection/ operation (If applicable) | | ī | | | |
| Го | 18.00 ENGINE | Check oil fluid level in the engine and make up tank | | ō | | | |
| Го | 19.00 ENGINE | Check coolant level in radiator and overflow tank | | ā | | | |
| | 20.00 ENGINE | Check cooling assembly for leaks | | | | | |
| | 21.00 ENGINE | Check engine for any fluid leaks | | | | | |
| | 22.00 ENGINE | Check Exhaust for leaks/restrictions/mounting | | | | | |
| | 23.00 ENGINE | Inspect all belts condition and verify proper tension | | | | | |
| | 24.00 ENGINE | Inspect cooling assembly and clean as necessary | | | | | |
| | 25.00 ENGINE | Inspect CCV filter and canister for water or restrictions | | | | | |
| _ | 26.00 ENGINE | Check Battery water level | | | | | |
| | | | | | | | |
| | 27.00 ENGINE | Load test Battery | | | | | |
| | 28.00 ENGINE | Inspect air filter and replace as necessary | | | | | |
| | 29.00 ENGINE | Inspect Maxitrol fuel filter, replace as necessary | | | | | |
| _ | 30.00 ENGINE | Complete all due Preventative Maintenance | | | | | |
| <u>To</u> | 31.00 ELECTRICAL COMPONENTS | Inspect the threads on aluminum lugs attached to knife switch | | | | | |
| <u>To</u> | 32.00 ELECTRICAL COMPONENTS | Verify torque of fasteners on phase connections in Alternator | | | | | |
| <u>To</u> | 33.00 ELECTRICAL COMPONENTS | Verify torque on top and bottom breaker phase connections | | | | | |
| <u> </u> | 34.00 ELECTRICAL COMPONENTS | Check the fasteners holding inner fastening plate inside breaker panel | | | | | |
| <u>To</u> | 35.00 CABINET & FUEL SUPPLY | Ensure fuel selection switch is in AUTO | | | | | |
| <u>To</u> | 36.00 CABINET & FUEL SUPPLY | Ensure the fasteners securing the cabinet skid to trailer are present and tight | | | | | |
| <u>To</u> | 37.00 CABINET & FUEL SUPPLY | Inspection of all vapor and LP fuel piping, ensure no leaks | | | | | |
| | 38.00 CABINET & FUEL SUPPLY | Inspect LP Vaporizers for leaks | | | | | |
| <u>To</u> | 39.00 CABINET & FUEL SUPPLY | Ensure the separator and/or volume tank are drained | | | | | |
| <u> </u> | 40.00 CABINET & FUEL SUPPLY | Ensure all fuel pressure gauges are operational and accurate Ensure the lb_and_oz_regulator are both operating correctly | | | | | |

INTERNAL USE ONLY