



FLAMELESS HEATERS

Features

- Meets or exceeds all EPA standards
- Temperature rise up to 180°F
- Output air volume up to 3,500, (550F) and 5,500 (750F) cubic feet per minute at 5.0" static pressure
- Heavy-duty steel construction
- Easy push-button operation
- Equipped with the Gravity asset management tool for remote monitoring of location and performance
- Proactive maintenance program for ultimate reliability

Applications

- Oil and gas exploration and construction services
- Rig-floor heating
- Keep drilling platform cellars warm and ice-free
- Work-over rigs
- Pre-warming of equipment and motors
- Emergency thawing
- Warming employee lockers and housing

Efficient, clean, safe, high output flameless air heat.

Gravity flameless mobile heaters are specifically designed to safely provide powerful heat in environments in which an open flame could be hazardous. The interface system is easy to use and allows you to set a temperature that will remain reliable and consistent.

Each unit is lockable, provides 110% containment, and the engine is protected because it is never loaded until it is warmed to the ideal level, so that you're never stuck out in the cold.



FLAMELESS HEATER SPECIFICATIONS

Specifications		
Heater Size	MAC 550 F	MAC 750 F
Fuel Rate (gph)	3.00	3.55
Fuel Capacity	125 gallon tank	160 gallon tank
Temperature rise	180°F	180°F
Output Air Volume CFM @5" SP	1,400 - 3,500	2,650 - 5,500
Power (self Contained)	self-powered/diesel	self-powered/diesel
Length	178"	178"
Width	72"	72"
Height	75"	80"
Weight	3,800 lbs.	4,300 lbs.
Operating Time	40+ hours	30+ hours